

EUROLITE LED TMH-X Bar 5 Moving-Head Beam

Narrow beam LED Moving Bar with 5 RGBW LEDs (15 W each) and unlimited TILT

Art. No.: 51785905

GTIN: 4026397613902



The article is no longer in our assortment.

Features:

- Moving Beam bar equipped with five 15 W COB LEDs with RGBW colors
- Each LED can be controlled individually
- Narrow beam angle
- With Infinity function for unlimited TILT movement
- Positioning within 540° PAN and 360° TILT
- Automatic position correction for PAN
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Colored beams in red, green, blue and white
- Stepless RGBW color mixture
- Color presets
- Strobe effect with variable speed
- Internal programs
- Exact positioning via 16 bit PAN/TILT movement resolution
- Dimmer
- Control board with LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 5 powerful LEDs 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Fan effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free

Logistic

EAN / GTIN: 4026397613902

Weight: 10,00 kg

Length: 0.48 m

Width: 0.39 m

Height: 0.27 m

- With a beam angle of 3°
- Multicolor LCD display

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	5 x 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	360° Exact positioning (16 bit resolution) plus infinity
Max. PAN movement:	540° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	0 - 18 Hz
DMX channels:	16; 32
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; Sound to light via Microphone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	3°
Beam angle (1/2 peak):	3°
Beam angle (1/10 peak):	7°
Illuminance in Lux (lx):	Red (R) 3m: 1646 lx, 6m: 532 lx Green (G) 3m: 4112 lx, 6m: 1249 lx Blue (B) 3m: 1120 lx, 6m: 345 lx Cold white (CW) 3m: 6739 lx, 6m: 2089 lx All 3m: 10763 lx, 6m: 3175 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 43 cm Depth: 19,5 cm Height: 30 cm
Weight:	8,90 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting