

EUROLITE LED TMH-W120 Hypno Moving Head Wash

Compact LED moving head wash with 120 W RGB/WW LED and backlighting via RGB hypno LEDs

Art. No.: 51785928

GTIN: 4026397740110



List price: 355.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 120 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- 26 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- Positioning within 540° PAN, 200° TILT
- Exact positioning (16 bit resolution)
- Dimmer; dimmer curves adjustable
- Wash effect
- The device is cooled by temperature-controlled fan at the Head; low-noise cooling fan at the base
- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRM by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function
- Preprogrammed in Light Captain
- Flicker-free
- DMX fail mode (hold; zero values)
- With a beam angle of 11°
- With omega bracket
- 4 digit 7-segment LED display
- 4 x rubber feet
- Mains input and output for power linking up to 8 units

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket

Logistic

EAN / GTIN: 4026397740110

Weight: 4,00 kg

Length: 0.31 m

Width: 0.26 m

Height: 0.23 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix) 26 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
Max. TILT movement:	200° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	1 - 20 Hz
DMX channels:	23
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x temperature-controlled fan at the Head 1 x low-noise cooling fan at the base
Control:	Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function
Preprogrammed in:	Light Captain
Projection:	Flicker-free
PWM frequency:	20000 Hz
DMX fail mode:	Hold; zero values
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	20°
Illuminance in Lux (lx):	Red (R) 1m: 11680 lx, 3m: 1064 lx, 6m: 257 lx Green (G) 1m: 21059 lx, 3m: 1883 lx, 6m: 429 lx Blue (B) 1m: 4476 lx, 3m: 434 lx, 6m: 102 lx Warm white (WW) 1m: 19730 lx, 3m: 1711 lx, 6m: 408 lx All 1m: 52623 lx, 3m: 4746 lx, 6m: 1108 lx
Housing color:	Black
Attachment system:	Omega bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Transport aid:	4 x rubber feet
Diameter mounting holes:	1 x Ø10mm

Material:	Plastic
Dimensions:	Width: 20 cm Depth: 14 cm Height: 29 cm
Weight:	3,60 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting