

EUROLITE LED TMH-W400 Moving Head Wash Zoom

Bright washlight with 400 W COB LED and motorized zoom

Art. No.: 51785930

GTIN: 4026397700138



List price: 1069.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 400 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
- Positioning within 540° PAN, 230° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Color blend stepless; Dimmer electronic
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain; Light´J
- Flicker-free
- With a beam angle of 9° - 48°
- Very high color rendering index (CRI)
- Multicolor LCD display
- Mains input and output for power linking up to 4 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

Logistic

EAN / GTIN: 4026397700138

Weight: 11,40 kg

Length: 0.48 m

Width: 0.33 m

Height: 0.37 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	360 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 400 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Max. TILT movement:	230° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 25 Hz
Equipment:	Zoom motor driven
DMX channels:	13
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	9° - 48°
Beam angle (1/2 peak):	9 - 25°
Beam angle (1/10 peak):	16 - 48°
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Narrow red (R) 1m: 14250 lx, 3m: 2003 lx, 6m: 470 lx Narrow green (G) 1m: 36558 lx, 3m: 4533 lx, 6m: 1085 lx Narrow blue (B) 1m: 4869 lx, 3m: 959 lx, 6m: 235 lx Narrow warm white (WW) 1m: 33844 lx, 3m: 3508 lx, 6m: 837 lx Narrow all 1m: 75609 lx, 3m: 9660 lx, 6m: 2293 lx Wide red (R) 1m: 2821 lx, 3m: 359 lx, 6m: 97 lx Wide green (G) 1m: 6107 lx, 3m: 809 lx, 6m: 227 lx Wide blue (B) 1m: 1410 lx, 3m: 188 lx, 6m: 53 lx Wide warm white (WW) 1m: 5425 lx, 3m: 706 lx, 6m: 195 lx Wide all 1m: 13817 lx, 3m: 1798 lx, 6m: 495 lx

Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 30,0 cm Depth: 23,0 cm Height: 45,0 cm
Weight:	10,20 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting