

EUROLITE LED TMH FE-1800 Beam/Flower Effect

RGBW Moving Head flower with large zoom range and 18 x 12 W LED

Art. No.: 51785957

GTIN: 4026397554441



The article is no longer in our assortment.

Features:

- Equipped with 18 x 12 W COB LED with RGBW colors, distributed in 6 segments
- Each segment can be controlled individually via DMX
- 20 or 40 DMX channels selectable
- Functions: colored beams in R, G, B and W, preset colors, built-in program, strobe effect with variable speed, dimmer, sound-control, Master/Slave operation
- Adjustable zoom movement - from narrow single beam to room-filling beams - via rotating lens
- Different patterns and movements can be selected via DMX
- Stepless RGBW color mixture
- Positioning within 540° PAN and 190° TILT
- PAN-angle switchable between 540° and 360°
- Dimmer speed (step response) adjustable
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Control board with LC display for adjusting the DMX-starting address, PAN/TILT reverse, reset
- Neutrik powerCON terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 18 powerful LEDs 12 W COB (chip-on-board) 4in1 QCL RGBW
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Multi beam effect; beam effect
- The device is cooled by cooling fan
- Control via DMX; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain

Logistic

EAN / GTIN: 4026397554441

Weight: 11,75 kg

Length: 0.42 m

Width: 0.48 m

Height: 0.33 m

- Flicker-free
 - With a beam angle of 6,5°
- Package contents**
- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x xLR cable

Technical specifications:

| | |
|------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 310 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray) |
| Lamp type: | LED lamp |
| LED: | 18 x 12 W COB (chip-on-board) 4in1 QCL RGBW |
| Max. TILT movement: | 190° Exact positioning (16 bit resolution) Auto position correction (feedback) |
| Max. PAN movement: | 540°, 360° Exact positioning (16 bit resolution) Auto position correction (feedback) |
| Flash rate: | 0 - 18 Hz |
| DMX channels: | 20; 40 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | DMX; Sound to light via Microphone |
| Preprogrammed in: | Light´J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 6,5° |
| Beam angle (1/2 peak): | 6,5° |
| Housing color: | Black |
| Dimensions: | Width: 33 cm Depth: 24 cm Height: 43 cm |
| Weight: | 10,45 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |