

EUROLITE LED TMH-15 Moving Head Zoom Wash

4in1 moving-head wash with zoom and 15 W QCL LEDs

Art. No.: 51785968 GTIN: 4026397544237











The article is no longer in our assortment.

Features:

- Equipped with seven 15 W quadcolor LEDs with RGBW colors
- Compact lightweight
- Motorized zoom with11°- 55° beam angle
- Color presets
- Positioning within 630° PAN and 200° TILT
- Stepless RGBW color mixture
- Masterdimmer
- Internal programs
- Strobe effect with 1-18 flashes per second
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-control via built-in microphone
- Control board with graphic LC display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- The device is cooled by cooling fan
- Control via DMX; stand-alone
- Preprogrammed in Light´J; LED PC-Control 512
- Flicker-free
- With a beam angle of 11° 55°

Logistic

EAN / GTIN: 4026397544237

Weight: 5,90 kg Length: 0.36 m Width: 0.33 m Heigth: 0.21 m

Technical specifications:

<u> </u>	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP20
Lamp type:	LED lamp
Cooling:	Cooling fan
Control:	DMX; stand-alone
Preprogrammed in:	Light'J; LED PC-Control 512
Projection:	Flicker-free
Beam angle:	11° - 55°
Beam angle (1/2 peak):	11 - 28°
Beam angle (1/10 peak):	25 - 55°
Illuminance in Lux (lx):	Narrow red (R) 3m: 702 lx, 6m: 182 lx Narrow green (G) 3m: 1131 lx, 6m: 298 lx Narrow blue (B) 3m: 185 lx, 6m: 50 lx Narrow cold white (CW) 3m: 1139 lx, 6m: 304 lx Narrow all 3m: 2272 lx, 6m: 600 lx Wide red (R) 3m: 157 lx, 6m: 42 lx Wide green (G) 3m: 238 lx, 6m: 65 lx Wide blue (B) 3m: 54 lx, 6m: 15 lx Wide cold white (CW) 3m: 329 lx, 6m: 91 lx Wide all 3m: 562 lx, 6m: 155 lx
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 15 cm Height: 33,5 cm
Weight:	5,35 kg
DMX channels:	13
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED type:	Cree 15 W QCL
LED number:	7
Maximum PAN-movement:	630°
Maximum TILT-movement:	
	200°
Beam angle:	200° 11° - 28°
Beam angle:	11° - 28°
Beam angle: Dimensions (L x W x H):	11° - 28°