

EUROLITE LED TMH-16 Moving Head Zoom Wash

Compact washlight with 10 W RGBW LEDs and large zoom range

Art. No.: 51785978

GTIN: 4026397585445



Features:

- Equipped with six 10W 4in1 LEDs in the colors red, green, blue and white
- Compact lightweight
- Functions: stepless RGBW color mixture, preset colors, built-in program, strobe effect with variable speed, dimmer, sound-control, Master/Slave operation
- Motorized zoom with 2-57° beam angle
- Positioning within 540° PAN and 190° TILT
- PAN-angle switchable between 540° and 360°
- Dimmer speed (step response) adjustable
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Control board with LCD for adjusting the DMX-starting address, PAN/TILT reverse, reset
- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 6 LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Fixtures available for Light 'J'; LED PC-Control 512; Light Captain
- Flicker-free

Logistic

EAN / GTIN: 4026397585445

Weight: 6,55 kg

Length: 0.32 m

Width: 0.29 m

Height: 0.39 m

Technical specifications:

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 80 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 6 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | 190° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540°, 360° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 0 - 18 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 15 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | DMX; stand-alone; sound to light via microphone |
| Fixtures available for: | Light'J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle (1/2 peak): | 2 - 31° |
| Beam angle (1/10 peak): | 7 - 57° |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 1071 lx, 6m: 266 lx Narrow green (G) 3m: 2417 lx, 6m: 608 lx Narrow blue (B) 3m: 523 lx, 6m: 135 lx Narrow cold white (CW) 3m: 3244 lx, 6m: 822 lx Narrow all 3m: 6846 lx, 6m: 1729 lx Wide red (R) 3m: 51 lx, 6m: 15 lx Wide green (G) 3m: 116 lx, 6m: 33 lx Wide blue (B) 3m: 26 lx, 6m: 8 lx Cold white (CW) 3m: 156 lx, 6m: 45 lx Wide all 3m: 328 lx, 6m: 94 lx |
| Housing color: | Black |
| Dimensions: | Width: 24.5 cm Depth: 19 cm Height: 33 cm |
| Weight: | 5.62 kg |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
1 x omega bracket

1 x XLR cable