

EUROLITE LED TMH-75 Hybrid Moving-Head Spot/Wash COB

Bright spotlight and full-fledged washlight with 75 W LED

Art. No.: 51785982

GTIN: 4026397612998



The article is no longer in our assortment.

Features:

- Equipped with a white 75 W COB LED and nine 8 W 6in1LEDs in the colors red, green, blue, amber, white and UV
- Compact lightweight
- 7 brilliant, dichroic colors plus white
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel with 6 rotating gobos plus open
- 3-facet prism (rotating)
- Preprogrammed scenes in Program Run for stand-alone operation
- Electronic dimmer
- Motorized focus
- Programmable color-change speed and strobe effect
- Stepless RGBAW+UV color mixture
- Color macros can be called up via DMX controller
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN-angle switchable between 540°, 360° and 180°
- TILT-angle switchable between 270°, 180° and 90°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT Reverse, Program, Reset
- Switch-mode power supply for operation between 100 and 240 Volts
- 9 powerful LEDs 8 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- 1 powerful LED 75 W COB (chip-on-board) cold white (CW)
- TILT angle switchable between 270° and 180°; and 90°
- PAN angle switchable between 540° and 360°; and 180°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)

Logistic

EAN / GTIN: 4026397612998

Weight: 9,55 kg

Length: 0.42 m

Width: 0.36 m

Height: 0.37 m

- Gobo wheel with rotating gobos; Prism 3-fold; Focus motor-driven
- Gobo effect; beam effect
- Color wheel with 7 dichroic filters plus open
- Gobo wheel with rotating gobos, 6 gobos and open
- The device is cooled by cooling fan
- Control via DMX; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
- With a beam angle of 12°

Package contents

- 1 x moving light, 2 x omega bracket, 4 x screw, 1 x user manual, 1 x power cord, 1 x xLR cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED:	9 x 8 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) 1 x 75 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270°, 180° Exact positioning (16 bit resolution) Auto position correction (feedback); , 90°
Max. PAN movement:	540°, 360° Exact positioning (16 bit resolution) Auto position correction (feedback); , 180°
Equipment:	Gobo wheel with rotating gobos; Prism 3-fold; Focus motor-driven
Color generation:	Color wheel with 7 dichroic filters plus open
Gobos:	Gobo wheel with rotating gobos, 6 gobos and open
DMX channels:	21
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; Sound to light via Microphone
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	12°
Beam angle (1/2 peak):	Spot 12° Wash effect 28°
Beam angle (1/10 peak):	45°
Illuminance in Lux (lx):	Wash effect red (R) 3m: 24 lx, 6m: 7 lx Wash effect green (G) 3m: 133 lx, 6m: 36 lx Wash effect blue (B) 3m: 20 lx, 6m: 6 lx Wash effect cold white (CW) 3m: 92 lx, 6m: 26 lx Wash effect amber (A) 3m: 31 lx, 6m: 9 lx Wash effect ultra violet (UV) 3m: 1 lx, 6m: 1 lx Wash effect all 3m: 288 lx, 6m: 78 lx Spot cold white (CW) 3m: 3942 lx, 6m: 1008 lx
Housing color:	Black

Dimensions:	Width: 25,5 cm Depth: 25 cm Height: 31 cm
Weight:	8,20 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting