

EUROLITE LED TMH-X5 Moving Head Wash Zoom

Washlight with 19 x 12 W LEDs, 4in1 QCL RGBW color mixing and motorized zoom

Art. No.: 51785990

GTIN: 4026397550788



The article is no longer in our assortment.

Features:

- Equipped with 19 x 12 W COB LED with RGBW colors, distributed in 3 segments
- Each segment can be controlled individually via DMX
- Positioning within 540° PAN and 270° TILT
- Stepless RGBW color mixture
- Dimmer
- Dimmer speed (step response) adjustable
- Motorized zoom with 1-55° beam angle
- Color presets
- Different patterns and movements can be selected via DMX
- Strobe effect with adjustable speed
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with LCD display for adjusting the DMX-starting address, PAN/TILT Reverse, Reset
- Neutrik PowerCon terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 19 powerful LEDs 12 W high-power 4in1 QCL RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 1° - 55°

Logistic

EAN / GTIN: 4026397550788

Weight: 12,30 kg

Length: 0.40 m

Width: 0.33 m

Height: 0.47 m

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x XLR cable, 2 x omega bracket

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	220 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray)
Lamp type:	LED lamp
LED type:	19 x 12 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Equipment:	Zoom motor driven
DMX channels:	20; 28
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	1° - 55°
Beam angle (1/2 peak):	1 - 28°
Beam angle (1/10 peak):	6 - 55°
Illuminance in Lux (lx):	Narrow red (R) 3m: 2753 lx, 6m: 699 lx Narrow green (G) 3m: 4727 lx, 6m: 1188 lx Narrow blue (B) 3m: 1159 lx, 6m: 300 lx Narrow cold white (CW) 3m: 6480 lx, 6m: 1678 lx Narrow all 3m: 11980 lx, 6m: 3074 lx
Housing color:	Black
Dimensions:	Width: 32 cm Depth: 22 cm Height: 44 cm
Weight:	11,10 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting