

## EUROLITE LED TMH Bar S120 Moving-Head Spots

LED lighting system with 4 individually controllable 30 W moving heads, gobo- and color wheel

Art. No.: 51786055

GTIN: 4026397728958



**List price: 950.81 €**

incl. 19% VAT.

### Features:

- 4 powerful LEDs 30 W COB (chip-on-board)
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution (optional)
- Gobo wheel with static gobos; Focus manual; color wheel
- Gobo wheel with static gobos, 7 gobos and open-shake effect
- Color wheel with 7 dichroic filters plus open-half colors selectable, Rainbow effect with adjustable speed
- Strobe effect; beam effect
- Positioning within 540° PAN and 180° TILT
- Exact positioning (16 bit resolution)
- Dimmer electronic
- Flicker-free
- With a beam angle of 13°
- Crossbar with integrated DMX control unit and stand sleeve
- With Omega bracket
- 4 digit 7-segment LED display
- Rubber feet
- The device is cooled by temperature-controlled fan
- Mains input and output for power linking up to 8 units
- Preprogrammed in Colorchief; Light J; Light Captain
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

### Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket, 2 x safety eyelet

### Logistic

EAN / GTIN: 4026397728958

Weight: 15,00 kg

Length: 1.08 m

Width: 0.34 m

Height: 0.26 m

## Technical specifications:

|                          |   |
|--------------------------|---|
| Power supply:            | 100-240 V AC, 50/60 Hz  |
| Power consumption:       | 100 W   |
| IP classification:       | IP20  |
| Protection class:        | Protection class I  |
| Power connection:        | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)  |
| Power output:            | P-Con (gray), mounting version  |
| Fuse:                    | 5 x 20 mm, T 2 A Fuse replaceable   |
| Lamp type:               | LED lamp  |
| LED:                     | 4 x 30 W COB (chip-on-board)  |
| Color temperature:       | 7300K   |
| Max. TILT movement:      | 180° Positioning; Exact positioning (16 bit resolution)   |
| Max. PAN movement:       | 540° Positioning; Exact positioning (16 bit resolution)   |
| Equipment:               | Gobo wheel with static gobos; Focus manual; color wheel   |
| Color generation:        | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed  |
| Gobos:                   | Gobo wheel with static gobos, 7 gobos and open Shake effect   |
| DMX channels:            | 3; 5; 9; 11; 17; 21; 30; 38   |
| DMX input:               | 3-pin XLR (M) mounting version  |
| DMX output:              | 3-pin XLR (F) mounting version  |
| Cooling:                 | Temperature-controlled fan  |
| Control:                 | Stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution (optional) |
| Preprogrammed in:        | Colorchief; Light´J; Light Captain  |
| Projection:              | Flicker-free  |
| Beam angle:              | 13°   |
| Beam angle (1/2 peak):   | 13°   |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 8899 lx, 3m: 856 lx, 6m: 205 lx   |
| Housing color:           | Black   |
| Attachment system:       | 2x Omega bracket  |
| Display type:            | 4 digit 7-segment LED display   |
| Transport aid:           | Rubber feet   |
| Dimensions:              | Width: 1 m<br>Depth: 17,5 cm<br>Height: 28,0 cm   |
| Weight:                  | 13,00 kg  |
| Noise classification:    | Class 3 (clearly perceptible sounds)  |

Legal specifications

---

Special product: Not designed for household room illumination

---

Intended use: Show effect lighting

---