

EUROLITE LED TMH Bar H240 Moving Head Beam/Flower

LED lighting system with 4 individually controllable 60 W moving heads with flower effect in RGBW

Art. No.: 51786057

GTIN: 4026397755497



List price: 950.81 €

incl. 19% VAT.

Description:

This bar combines four fully featured moving heads in a single system. Each unit is equipped with four 15 W LEDs with RGBW color mixing, allowing for both tight beams and room-filling flower effects.

The bar can be used flexibly: mounted on a stand, placed on the floor, or suspended from a truss. Special attention has been paid to ease of control, ensuring that even smaller DMX controllers can operate the bar efficiently. Dedicated modes are available that allow a wide range of positions, movements, chases, and effects to be created using only a few DMX channels. A great example of a suitable controller is the Eurolite Color Chief, which pairs perfectly with this bar.

Features:

- 16 LEDs 15 W SMD 6065 4in1 QCL RGBW
4 moving lights effects controlled separately
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Lens rotation
- Dimmer electronic; Motion macros adjustable; color selection; color macros adjustable
- Flower effect; beam effect
- 22 integrated show programs
- The device is cooled by cooling fan at the base; cooling fan at the head
- Control via stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 2°

Logistic

EAN / GTIN: 4026397755497

Weight: 14,25 kg

Length: 1.08 m

Width: 0.32 m

Height: 0.22 m

- With omega bracket
- Monochrome 4 digit 7-segment LED display
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile use; stage; mobile djs / entertainer; restaurants, bars and hotels; party room
- Application possibility: Standing; suspended
- Fixtures available for Light´J; Light Captain; Colorchief

Technical specifications:

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 225 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Cable construction: | 3 x 1.0 mm ² H05VV-F |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 16 x 15 W SMD 6065 4in1 QCL RGBW |
| Max. TILT movement: | 180° exact positioning (16 bit resolution) |
| Max. PAN movement: | 540° exact positioning (16 bit resolution) |
| Flash rate: | 2 - 15 Hz |
| Equipment: | Lens rotation |
| DMX channels: | 5; 9; 14; 16; 25; 29; 44; 52 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | 2 x cooling fan at the base 4 x cooling fan at the head |
| Control: | Stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light´J; Light Captain; Colorchief |
| Projection: | Flicker-free |
| PWM frequency: | 11000 Hz |
| DMX fail mode: | Hold; blackout |
| Beam angle: | 2° |
| Beam angle (1/2 peak): | 2 |
| Beam angle (1/10 peak): | 6 |
| Lamp life: | 20000 h |
| Housing color: | Black |
| Attachment system: | Tube: Ø 35mm 2x omega bracket |
| Display type: | Monochrome 4 digit 7-segment LED display |
| Control elements: | Power switch |
| USB port: | Type A |

| | |
|--------------------------|--|
| Transport aid: | 4 x rubber feet |
| Diameter mounting holes: | 2 x Ø10mm |
| Material: | Metal |
| Dimensions: | Width: 100 cm Depth: 17.5 cm Height: 26.0 cm |
| Weight: | 12.70 kg |
| Noise classification: | Class 2 (slight noise) |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 2 x safety eyelet