

EUROLITE LED TMH-17 Moving Head Spot

Compact moving head Spot with 30 W LED, gobos and color wheel

Art. No.: 51786065

GTIN: 4026397693522



List price: 267.75 €

incl. 19% VAT.

Features:

- Compact lightweight
- 1 powerful LED 30 W COB (chip-on-board) color wheel
- Positioning within 540° PAN, 200° TILT
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; focus manual
- Dimmer electronic
- Gobo effect; beam effect; strobe effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- With a beam angle of 12°
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; small rental
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 2 x screw, 4 x washer, 1 x safety eyelet

Logistic

EAN / GTIN: 4026397693522

Weight: 3,17 kg

Length: 0.28 m

Width: 0.22 m

Heigh: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) color wheel
Max. TILT movement:	200° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	2 - 23 Hz
Equipment:	Gobo wheel with static gobos; focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 7 gobos and open
DMX channels:	9; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	12°
Beam angle (1/2 peak):	12°
Illuminance in Lux (lx):	Cold white (CW) 3m: 1677 lx, 6m: 417 lx
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 17 cm Depth: 14,5 cm Height: 24 cm
Weight:	2,70 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting