

EUROLITE LED TMH-S60 Moving Head Spot wh

Compact Moving moving head with 60 W LED, gobos, color wheel and white housing

Art. No.: 51786073

GTIN: 4026397713213



List price: 427.21 €

incl. 19% VAT.

Features:

- 3 gobos with heart patterns for exchange included
- 1 powerful LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 180° TILT
- Gobo wheel with rotating gobos; focus manual; color wheel
- Dimmer electronic
- Beam effect; strobe effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
slot-in gobo system for easy gobo replacement
- Shake effect
- 4 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; Light´J
- Flicker-free
- With a beam angle of 12°
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended

Package contents

Logistic

EAN / GTIN: 4026397713213

Weight: 3,55 kg

Length: 0.29 m

Width: 0.21 m

Height: 0.27 m

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet, 3 x gobos

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 95 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Device fuse: | 5 x 20 mm, T 1,5 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 60 W COB (chip-on-board) cold white (CW) |
| Max. TILT movement: | 180° positioning |
| Max. PAN movement: | 540° positioning |
| Equipment: | Gobo wheel with rotating gobos; focus manual; color wheel |
| Color generation: | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 13,8mm Image diameter 11mm Slot-in gobo system for easy gobo replacement Shake effect |
| DMX channels: | 10; 12 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional) |
| Preprogrammed in: | LED PC-Control 512; EASY SHOW 1; Light Captain; Light J |
| Projection: | Flicker-free |
| Beam angle: | 12° |
| Beam angle (1/2 peak): | 12° |
| Color temperature: | 7700K |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 15205 lx, 3m: 1764 lx, 6m: 445 lx |
| Housing color: | White |
| Display type: | 4 digit 7-segment LED display |
| Transport aid: | Rubber feet |
| Dimensions: | Width: 17,0 cm Depth: 15,0 cm Height: 24,0 cm |

| | |
|-----------------------|--|
| Weight: | 3,15 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |