

EUROLITE LED TMH-B90 Moving Head Beam

LED moving head beam with color wheel, static gobo wheel, prism and focus

Art. No.: 51786080

GTIN: 4026397692556



List price: 593.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 90 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 200° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Color wheel; gobo wheel with static gobos; focus motor-driven; prism 8-fold rotating; frost filter
- Dimmer electronic
- Beam effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 13 gobos und open
shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain; EASY SHOW 3; Light´J
- Flicker-free
- With a beam angle of 3°
- Good color rendering index (CRI)
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet

Logistic

EAN / GTIN: 4026397692556

Weight: 7,40 kg

Length: 0.36 m

Width: 0.32 m

Heigh: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 90 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	200° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	2 - 20 Hz
Equipment:	Color wheel; gobo wheel with static gobos; focus motor-driven; prism 8-fold rotating; frost filter
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 13 gobos und open Shake effect
DMX channels:	14
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; EASY SHOW 3; Light´J
Projection:	Flicker-free
Beam angle:	3°
Beam angle (1/2 peak):	3°
Color rendering index (CRI):	80 Ra
Illuminance in Lux (lx):	Cold white (CW) 3m: 33839 lx, 6m: 10454 lx
Housing color:	Black
Display type:	LCD display
Dimensions:	Width: 25,5 cm Depth: 20,5 cm Height: 33,0 cm
Weight:	6,55 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting