

EUROLITE LED TMH-B120 Hypno Moving Head Beam

LED moving head beam with hypno ring, color wheel, static gobo wheel, prism and focus

Art. No.: 51786081

GTIN: 4026397738513



List price: 772.31 €

incl. 19% VAT.

Features:

- 1 powerful LED 120 W COB (chip-on-board) cold white (CW)
- 30 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- Positioning within 540° PAN, 240° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Color wheel; gobo wheel with static gobos; focus motor-driven; frost filter; prism 8-fold rotating
- Dimmer
- Beam effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 13 gobos und open
shake effect
- 4 integrated show programs
- The device is cooled by cooling fan at the base; cooling fan at the Head
- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function
- Preprogrammed in Light Captain
- Flicker-free
- DMX fail mode (hold; zero values)
- With a beam angle of 2°
- With omega bracket
- Multicolor LCD display
- 2 Rugged carrying handles
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; rental

Logistic

EAN / GTIN: 4026397738513

Weight: 7,80 kg

Length: 0.43 m

Width: 0.30 m

Height: 0.34 m

- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x power cord, 1 x omega bracket, 1 x safety eyelet, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	170 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	1,1 m
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) cold white (CW) 30 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
Max. TILT movement:	240° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 20 Hz
Equipment:	Color wheel; gobo wheel with static gobos; focus motor-driven; frost filter; prism 8-fold rotating
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 13 gobos und open Shake effect
DMX channels:	21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan at the base 1 x cooling fan at the Head
Control:	Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function
Preprogrammed in:	Light Captain
Projection:	Flicker-free
DMX fail mode:	Hold; zero values
Beam angle:	2°
Beam angle (1/2 peak):	Beam 2° Ring 120°
Beam angle (1/10 peak):	Beam 2° Ring 120°

Color temperature:	8500K
Housing color:	Black
Attachment system:	Omega bracket
Display type:	Multicolor LCD display
Status LED:	DMX, fault
USB port:	Type A
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Material:	Plastic
Dimensions:	Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm
Weight:	6,95 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting