

## EUROLITE LED TSL-200 Scan COB

Scanner with 20 W COB LED, rotating gobos and color wheel

Art. No.: 51786123

GTIN: 4026397390742



**The article is no longer in our assortment.**

### Features:

- Equipped with a 20 W COB LED
- Long LED life
- Comparable to the light output of a 250 W halogen lamp
- DMX-controlled operation or stand-alone operation with Master/Slave function (up to 4 slaves)
- 14 motion macros can be called up via DMX controller
- Microphone-sensitivity adjustable via rotary-control
- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- Strobe effect with 1-18 flashes per second
- Strobe effect with adjustable speed
- Random strobe effect
- Manual focus
- Dimmer
- Small and portable
- Lightbeam with 13° radiation angle
- Control board with 4-digit display for adjusting the DMX-starting address, Pan/Tilt-Reverse
- 6.3 mm jack socket for remote control
- Blackout, gobos, colors and Auto/Manual Mode applicable in Stand Alone mode via optional EUROLITE RC-1 remote control
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via any standard DMX controller
- 1 powerful LED 20 W COB (chip-on-board) cold white (CW)
- Focus manual
- Gobo effect

### Logistic

EAN / GTIN: 4026397390742

Weight: 7,20 kg

Length: 0.48 m

Width: 0.28 m

Height: 0.30 m

- Color wheel with 7 dichroic filters plus open<BR>Rainbow effect with adjustable speed in both directions
  - Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
  - The device is cooled by cooling fan
  - Control via DMX; stand-alone; Sound to light via Microphone
  - Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain
  - With a beam angle of 13°
  - 4 digit 7-segment LED display
- Package contents**
- 1 x light effect, 1 x user manual, 1 x power cord

## Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	70 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED:	1 x 20 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 18 Hz
Equipment:	Focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 25mm Image diameter 20mm Shake effect
DMX channels:	9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	13°
Beam angle (1/2 peak):	13°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 20,5 cm Depth: 39 cm Height: 30 cm
Weight:	6,20 kg
<b>Legal specifications</b>	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting