

EUROLITE LED Twin Scan Bar

LED Scan Bar with 2 full-fledged scanners, incl. IR remote control

Art. No.: 51786200

GTIN: 4026397708127



List price: 593.81 €

incl. 19% VAT.

Features:

- 2 powerful LEDs 37,5 W COB (chip-on-board) cold white (CW) moving lights effects controlled separately
- Positioning within PAN and TILT
- Gobo wheel with static gobos; color wheel
- Color wheel with 7 dichroic filters plus open half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with static gobos, 7 gobos and open
- 16 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; Sound to light via Microphone; Master/slave function; IR remote control; Rotary dial for microphone sensitivity; Rotary dial for brightness; DMX; QuickDMX (optional); WDMX by wireless solution (optional); CRMX by LumenRadio (optional)
- The article is delivered pre-assembled
- With a beam angle of 12°
- Multicolor OLED display
- For application areas such as: Wedding/gala/events; Party room; mobile djs / entertainer
- Color selection; Dimmer electronic
- Strobe effect
- With Omega bracket
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3; Light´J
- Application possibility: On stand; suspended

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x remote control, 1 x battery, 1 x bag

Logistic

EAN / GTIN: 4026397708127

Weight: 6,85 kg

Length: 0.66 m

Width: 0.16 m

Height: 0.34 m

Technical specifications:

| | |
|------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 125 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray) |
| Device fuse: | 5 x 20 mm, T 3,15 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 2 x 37,5 W COB (chip-on-board) cold white (CW) |
| Color temperature: | 8500K |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Gobo wheel with static gobos; color wheel |
| Color generation: | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed |
| Gobos: | Gobo wheel with static gobos, 7 gobos and open |
| DMX channels: | 2; 5; 7; 8; 14 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | 2 x temperature-controlled fan |
| Control: | Stand-alone; Sound to light via Microphone; Master/slave function; IR remote control; Rotary dial for microphone sensitivity; Rotary dial for brightness; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional) |
| Preprogrammed in: | Light Captain; EASY SHOW 2; EASY SHOW 3; Light J |
| Beam angle: | 12° |
| Beam angle (1/2 peak): | 12° |
| Housing color: | Black |
| Attachment system: | Omega bracket |
| Display type: | Multicolor OLED display |
| Dimensions: | Length: 60 cm Width: 11,8 cm Height: 28,5 cm |
| Weight: | 6,25 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |