

## EUROLITE TMH BSW-380 Moving-Head Beam/Spot/Wash

Art. No.: 51786850

Beam/spot/wash moving-head with 371W discharge lamp, color wheel, gobo wheels, prisms, frost, focus and zoom

GTIN=4026397701142



**List price: 2021.81 €**

incl. 19% VAT.

### Features:

- Beam effect; spot effect; Wash effect
- Light source: Osram Sirius HRI 371W discharge lamp
- Lamp installed and adjusted ex factory
- Additional frost filter provides a wide, soft and homogeneous light
- Positioning within 540° PAN and 230° TILT
- Auto position correction (feedback)
- Exact 16 bit resolution at zoom, focus
- Exact positioning (16 bit resolution)
- Prism 16-fold; Prism 8-fold rotating; Prism 16-fold rotating; gobo wheel with static gobos; gobo wheel with rotating gobos; Focus motor-driven; Zoom motor-driven; frost filter; Dimmer
- Color wheel with 13 dichroic filters plus open<BR>Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
- Slot-in gobo system for easy gobo replacement
- Gobos changeable
- Gobo wheel with static gobos, 11 gobos and open<BR>shake effect
- Gobo wheel with static gobos, 5 gobos and open<BR>shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 4° - 35°
- Multicolor LCD display,<BR>with battery buffering for easy controlling
- Mains input and output for power linking up to 4 units
- Color animations; patterns

### Logistic

EAN / GTIN: 4026397701142  
Weight: 25,30 kg  
Length: 0.54 m  
Width: 0.50 m  
Height: 0.64 m

- Preprogrammed in Light Captain
- For application areas such as: Clubs/dancing school; Stage; Rental
- Application possibility: Standing; suspended

#### Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

### Technical specifications:

|                        |  |
|------------------------|--|
| Power supply:          | 100-240 V AC, 50/60 Hz   |
| Power consumption:     | 490 W  |
| IP classification:     | IP20   |
| Protection class:      | Protection class I   |
| Power connection:      | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)   |
| Power output:          | P-Con (gray), mounting version   |
| Fuse:                  | 5 x 20 mm, T 8 A   |
| Lamp type:             | Discharge lamp   |
| Max. TILT movement:    | 230° Exact positioning (16 bit resolution) Auto position correction (feedback)   |
| Max. PAN movement:     | 540° Exact positioning (16 bit resolution) Auto position correction (feedback)   |
| Flash rate:            | 1 - 18 Hz  |
| Equipment:             | Prism 16-fold; Prism 8-fold rotating; Prism 16-fold rotating; gobo wheel with static gobos; gobo wheel with rotating gobos; Focus motor-driven; Zoom motor-driven; frost filter; Dimmer  |
| Color generation:      | Color wheel with 13 dichroic filters plus open Rainbow effect with adjustable speed in both directions   |
| Gobos:                 | Gobo wheel with rotating gobos, 7 gobos and open<br>Shake effect<br>Outside diameter 22,5mm<br>Image diameter 12mm<br>Slot-in gobo system for easy gobo replacement<br>Gobos changeable<br>Gobo wheel with static gobos, 11 gobos and open<br>Shake effect<br>Gobo wheel with static gobos, 5 gobos and open<br>Shake effect |
| DMX channels:          | 22; 26   |
| DMX input:             | 3-pin XLR (M) mounting version   |
| DMX output:            | 3-pin XLR (F) mounting version   |
| Cooling:               | Cooling fan  |
| Control:               | Stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)  |
| Preprogrammed in:      | Light Captain  |
| Beam angle:            | 4° - 35°   |
| Beam angle (1/2 peak): | Spot 4 - 35°   |

|                         |   |
|-------------------------|---|
| Beam angle (1/10 peak): | Spot 4 - 35°  |
| Housing color:          | Black   |
| Display type:           | Multicolor LCD display battery buffering            |
| Use of brands:          | OSRAM bulb included                                 |
| Dimensions:             | Width: 39,5 cm<br>Depth: 30,5 cm<br>Height: 63,0 cm |
| Weight:                 | 22,70 kg  |
| Noise classification:   | Class 3 (clearly perceptible sounds)                |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination        |
| Intended use:           | Show effect lighting                                |