

FUTURELIGHT LED PRO IP Flood 72

Weather-proof outdoor floodlight (IP65) with cold white high-power LEDs

Art. No.: 51833556

GTIN: 4026397616996



Features:

- High-quality die-cast housing for highest stability
- Particularly bright illuminating power of the LEDs with 150 lm/W
- 72 LEDs 5 W high-power cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 60°
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Stage

Logistic

EAN / GTIN: 4026397616996

Weight: 6,05 kg

Length: 0.39 m

Width: 0.35 m

Height: 0.27 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP65
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.5 m
Lamp type:	LED lamp
LED type:	72 x 5 W high-power cold white (CW)

Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	60°
Beam angle (1/10 peak):	120°
Color rendering index (CRI):	82 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Width: 28.3 cm Depth: 27 cm Height: 18.3 cm
Weight:	4.75 kg
Noise classification:	Class 0 (no noise at all)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:
