

## FUTURELIGHT WDS-CRMX TX IP Wireless DMX Transceiver Outdoor

Weather-proof wireless DMX transceiver, IP65

Art. No.: 51834031

GTIN: 4026397721942



**List price: 355.81 €**

incl. 19% VAT.

### Features:

- Transceiver, to be used as transmitter or receiver
- Control via W-DMX by wireless solution; CRMX by LumenRadio
- Adaptive frequency hopping ensures interference-free operation in the 2.4 GHz band
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Operating range up to 600m with line-of-sight
- Multicolored LED indicator
- Lockable power input (IP T-Con)
- 2.4 GHz license-free worldwide
- With Omega bracket
- OLED display
- Suitable for outdoor use IP65
- Up to 10 transmitters can be operated in parallel without interference

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397721942

Weight: 1,55 kg

Length: 0.30 m

Width: 0.20 m

Height: 0.14 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 1,6 W

IP classification: IP65

Protection class: Protection class I

Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
DMX channels:	Input 512 Output 512
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Control:	W-DMX by wireless solution; CRMX by LumenRadio
Range:	Range up to 600m with line-of-sight
Frequency band:	2.4 GHz
Parallel mode:	Max. 10 transmitter
Antenna gain:	5 dBi
Modulation:	GFSK
Attachment system:	Omega bracket
Display type:	OLED display
Status LED:	DMX, level meter
Color:	Black
Dimensions:	Length: 17,3 cm Width: 15,6 cm Height: 9,2 cm
Weight:	1,30 kg