

FUTURELIGHT PHS-1200E Moving-Head

High performance Moving Head

Art. No.: 51838400

GTIN: 4026397198690



The article is no longer in our assortment.

Features:

- With electronic ballast
- With integrated wireless receiver for W-DMX operation
- Extreme light output of 1200 W
- Multi-lens-system for extremely bright and clear projections
- CMY color mixing for indefinite color variations
- Motorized color-wheel with 4 different, dichroic color-filters and white and additionally with correction-filter CTB and UV-filter
- The color-wheel can be individually equipped with colors/gobos
- Rainbow effect with adjustable speed in both directions
- Preprogrammed color- and gobo-macros
- Variable color temperature correction via CTO-filter
- Stepless frost-filter for fading the projection in or out
- Slot-in gobo-system for exchanging gobos without tools
- Two gobo-wheels with 5 rotating gobos plus open each
- All gobos can be interchanged
- With gobo-shake function
- Effect-wheel with rotating 2-facet prism, 3-facet prism, 5-facet prism, 3D-prism and open
- The prisms rotate in both directions and at different speeds, prism index function
- Macro-function for rotating gobos/rotating prism combinations
- Animation-wheel for fire effect
- Motorized focus
- Mechanic dimmer
- Motorized zoom
- Steplessly adjustable iris
- Preprogrammed variable/random iris/dimmer/shutter pulse effects
- Strobe effect with 1-10 flashes per second via shutter

Logistic

EAN / GTIN: 4026397198690

Weight: 54,20 kg

Length: 0.60 m

Width: 0.60 m

Height: 1.06 m

Bulky product

- Random strobe effect
- Lightbeam with 17°-32° radiation angle
- Colored LCD-display
- ESDC-Function (Easy Service Data Check) with battery-buffered Control Board for operation time readouts etc.
- Control board with LCD-display and encoder for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 64 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- Automatic position correction
- 8 or 16 bit resolution
- Lamp already installed and adjusted from factory
- DMX control via every standard DMX controller
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	1300,00 W
DMX channels:	26
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	13 Hz
Color-system:	CMY color-mixture
Color-wheel:	4 dichroic, correction-filter CTB, UV-filter + white
Color temperature:	2900 K - 6000 K
Rotating gobo-wheel 1:	5 gobos and open
Rotating gobo-wheel 2:	5 gobos and open
Outside diameter of the gobos:	37.4 mm
Image diameter of the gobos:	31 mm
Maximum PAN-movement 630°:	in 3.5 s
Maximum TILT-movement 265°:	in 2.5 s
Length of base (including handles):	540 mm
Width of yoke:	500 mm
Height (head horizontal):	650 mm
Weight:	51 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting