


FUTURELIGHT PLS-15R Moving-Head

Brilliant multi-function moving-head with Philips Platinum 15R lamp

Art. No.: 51838920

GTIN: 4026397471854



The article is no longer in our assortment.

Features:

- Double lamp lifetime with half power input and smaller dimensions compared to a 700 W lamp
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Supports RDM (Remote Device Management)
- 21, 23 or 34 DMX channels selectable
- Color-wheel with 4 different, dichroic color filters and white and additionally with CTO correction filter and UV filter
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- CMY color mixing
- Rainbow effect with adjustable speed in both directions
- Macro-function for combinations between CMY color mixing and color-wheel
- Gobo-wheel with 14 static metal gobos plus open
- Gobo-wheel with 8 rotating gobos plus open
- Slot-in gobo-system for exchanging gobos without tools
- With gobo-shake function
- Rotating 3-facet prism
- Macro-function for rotating gobos/rotating prism combinations
- Steplessly adjustable iris
- Motorized focus
- Motorized zoom with 8°-26° beam angle
- Strobe effect with 1-13 flashes per second
- Random strobe effect
- Stepless frost-filter for fading the projections in or out
- Mechanic dimmer
- Exact positioning via 16 bit resolution: CMY, color-wheel, gobo indexing, prism indexing, focus, zoom, dimmer, iris and PAN/TILT movement
- Automatic position correction

Logistic

EAN / GTIN: 4026397471854

Weight: 28,65 kg

Length: 0.76 m

Width: 0.51 m

Height: 0.46 m

- Switch-mode power supply
 - Automatic power supply adaption between 100 and 240 Volts without power selector
 - ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc.
 - Control board with graphic LCD display and touch keyboard for adjusting the DMX-starting address, PAN/TILT reverse, program, reset, lamp on/off, operating hours
 - PAN-angle switchable between 630° and 540°
 - DMX-controlled operation or stand-alone operation with master/slave function
 - 7 built-in programs can be called up via DMX-controller
 - 56 preprogrammed scenes in Program Run for stand alone operation
 - Number of scenes in Program Run can be changed individually
 - The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
 - Software upload by optional accessory via DMX link
 - Sound-controlled via built-in microphone
 - With PHILIPS MSD Platinum 15R discharge lamp
 - The integral mounting plate on the bottom of the device enables a permanent installation even without omega clamps, e.g. on the ceiling
 - Power connection via Neutrik PowerCon jack and included power cable
 - DMX-control via every standard DMX-controller
- device**
- Cordless, flexible and versatile
- Package contents**
- 1 x device

Technical specifications:

| | |
|-------------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 500,00 W |
| Device | |
| Battery pack type: | 1 x lithium ion 3,7 V, 1,85 Wh |
| DMX channels: | 21/23/34 |
| DMX connection: | 5-pin and 3-pin XLR |
| Wireless signal transmission: | 2.4 GHz (ISM) |
| Flash-rate: | 13 Hz |
| Color-wheel: | 4 dichroic plus white, CTO correction filter, UV filter |
| Static gobo wheel: | 14 gobos and open |
| Rotating gobo wheel: | 8 gobos and open |
| Outside diameter of the gobos: | 16 mm |
| Image diameter of the gobos: | 10 mm |
| Maximum PAN-movement 630°: | in 1.5 s |
| Maximum TILT-movement 270°: | in 1.0 s |
| Beam angle: | 8°-26° |
| Length of base (including handles): | 391 mm |
| Width of yoke: | 331 mm |
| Height (head horizontal): | 559 mm |
| Weight: | 23.5 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |