

## FUTURELIGHT PLB-230 Moving Head

High performance beam with Osram Sirius HRI 230 W lamp and LED ring with RGB color mixture

Art. No.: 51838951

GTIN: 4026397484120



**The article is no longer in our assortment.**

### Features:

- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Strobe effect with adjustable speed
- Random strobe effect
- Electronic dimmer (0-100%)
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Number of scenes in Program Run can be changed individually
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- With already installed Osram Sirius HRI 230 W lamp
- 12 powerful LEDs 3 W 3in1 TCL RGB
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; focus motor-driven
- Gobo effect
- Color wheel with 14 dichroic filters plus open<BR>rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 8 gobos and open<BR>shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone

### Logistic

EAN / GTIN: 4026397484120

Weight: 18,10 kg

Length: 0.61 m

Width: 0.44 m

Height: 0.36 m

- Preprogrammed in LED PC-Control 512; Light Captain; Light´J
- With a beam angle of 1,3°

## Technical specifications:

|                        |  |
|------------------------|--|
| Power supply:          | 100-240 V AC, 50/60 Hz   |
| Power consumption:     | 325,00 W   |
| IP classification:     | IP20   |
| Power connection:      | Mains input via PowerCON (blue), mounting version power supply cord with safety plug   |
| Lamp type:             | Discharge lamp   |
| LED type:              | 12 x 3 W 3in1 TCL RGB  |
| Max. TILT movement:    | 270° exact positioning (16 bit resolution) auto position correction (feedback)   |
| Max. PAN movement:     | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)   |
| Flash rate:            | 0 - 20 Hz  |
| Equipment:             | Gobo wheel with rotating gobos; focus motor-driven   |
| Color generation:      | Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions   |
| Gobos:                 | Gobo wheel with rotating gobos, 8 gobos and open<br>Outside diameter 14mm<br>Image diameter 6mm<br>Shake effect<br>Gobos changeable<br>Slot-in gobo system for easy gobo replacement |
| DMX channels:          | 17; 19; 21; 24   |
| DMX input:             | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version   |
| DMX output:            | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version   |
| Cooling:               | Temperature-controlled fan   |
| Control:               | RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone   |
| Preprogrammed in:      | LED PC-Control 512; Light Captain; Light´J   |
| Carrier frequency:     | 2,4 GHz  |
| Beam angle:            | 1,3°   |
| Beam angle (1/2 peak): | 1,3°   |
| Housing color:         | Black  |
| Dimensions:            | Width: 25 cm<br>Depth: 42,4 cm<br>Height: 34,3 cm  |
| Weight:                | 16,20 kg   |
| Noise classification:  | Class 3 (clearly perceptible sounds)   |
| Legal specifications   |  |
| Special product:       | Not designed for household room illumination   |

Intended use:

Show effect lighting