

FUTURELIGHT EYE-7.i LED Moving Head Beam

4in1 moving head beam with unlimited PAN and TILT movement

Art. No.: 51841306

GTIN: 4026397513509



Features:

- Equipped with 7 x 15 W quadcolor LED with RGBW colors
- Compact housing
- Narrow illumination angle
- High PAN/TILT speed and Infinity function (.i) for unlimited PAN and TILT movement
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity and colors
- Master dimmer
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- 7 LEDs 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Beam effect
- The device is cooled by temperature-controlled fan

Logistic

EAN / GTIN: 4026397513509

Weight: 7,95 kg

Length: 0.46 m

Width: 0.32 m

Height: 0.27 m

- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
- Fixtures available for LED PC-Control 512
- With a beam angle of 7°

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110.00 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	7 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	Exact positioning (16 bit resolution) plus infinity auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) plus infinity auto position correction (feedback)
Flash rate:	0 - 18 Hz
DMX channels:	14; 15; 16; 22
DMX input:	1 x 5-pin XLR (M) mounting version
DMX output:	1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
Fixtures available for:	LED PC-Control 512
Beam angle:	7°
Beam angle (1/2 peak):	7°
Beam angle (1/10 peak):	12°
Illuminance in Lux (lx):	Red (R) 3m: 2714 lx, 6m: 611 lx Green (G) 3m: 4900 lx, 6m: 1161 lx Blue (B) 3m: 830 lx, 6m: 199 lx Cold white (CW) 3m: 5539 lx, 6m: 1294 lx All 3m: 12673 lx, 6m: 2948 lx
Housing color:	Black
Dimensions:	Width: 24.4 cm Depth: 17.9 cm Height: 35 cm
Weight:	6.80 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x omega bracket