

FUTURELIGHT EYE-60 LED Moving-Head Wash

Moving head wash with 3 W RGBW LEDs

Art. No.: 51841337

GTIN: 4026397391114



The article is no longer in our assortment.

Features:

- Equipped with 60 x 3 W LEDs: 22 x red, 17 x green, 15 x blue, 6 x white
- Correction of the color temperature via 6 cold white LEDs possible
- Long LED life
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Software-upload by optional FUTURELIGHT ULB-1 upload box via DMX link (from software version 2.0, 06/2010)
- Sound-controlled via built-in microphone
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 630° and 540°
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Stepless RGBW color changing
- Programmable color-change speed and strobe effect
- Random strobe effect
- Lightbeam with 22° radiation angle
- Blue LCD display
- ESDC function (Easy Service Data Check) with battery-buffered Control Board for operation time readouts etc.
- Strobe effect with 1-25 flashes per second
- Masterdimmer
- Rainbow effect

Logistic

EAN / GTIN: 4026397391114

Weight: 9,45 kg

Length: 0.36 m

Width: 0.30 m

Height: 0.44 m

- Control Board with LCD display and foil-keyboard for adjusting the DMX starting address, PAN/TILT Reverse, Program, Reset
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via every standard DMX controller
- Control via sound to light via microphone; RDM
device
- Cordless, flexible and versatile
Package contents
- 1 x device

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	250 W
Max. TILT movement:	265° positioning
Max. PAN movement:	630° positioning
Flash rate:	1 - 25 Hz
DMX channels:	13
Control:	Sound to light via microphone; RDM
Beam angle (1/2 peak):	22°
Dimensions:	Width: 31 cm Depth: 28,5 cm Height: 38,5 cm
Weight:	8 kg
Battery pack type:	1 x lithium ion 7,4 V, 2,24 Wh
DMX channels:	13
DMX connection:	3-pin XLR
Flash-rate:	25 Hz
Maximum PAN-movement 630°:	in 2.5 s
Maximum TILT-movement 265°:	in 1.5 s
LED number:	60
Beam angle:	22°
Dimensions (L x W x H):	310 x 285 x 385 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting