

FUTURELIGHT Stage Pixel Bar 10 WW

High performance LED bar with 17 W white light LEDs and dim-to-warm function

Art. No.: 51841357

GTIN: 4026397630886



The article is no longer in our assortment.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- 10 powerful LEDs 17 W COB (chip-on-board) Dim to warm (homogenous color mix) LEDs controlled separately
- Dimmer curves with adjustable response
- Integrated show programs
- The device is cooled by passive convection cooling
- Control via RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone
- Flicker-free
- With a beam angle of 20°
- Very high color rendering index (CRI)
- With Mounting bracket
- Built with NEUTRIK connector
- For application areas such as: Clubs/dancing school; Stage
- Strobe effect
- Preprogrammed in LED PC-Control 512; Light Captain; Light J
- Silent operation
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397630886

Weight: 11,50 kg

Length: 0.97 m

Width: 0.25 m

Height: 0.27 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 185 W

IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	10 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Color temperature:	3000K
Flash rate:	0 - 18 Hz
DMX channels:	2; 10; 12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Network connection:	Protocol: ArtNet 3 via 2x RJ-45 etherCON (F) mounting version
Cooling:	Passive convection cooling
Control:	RDM; ArtNet; stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Color rendering index (CRI):	91 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Use of brands:	Built with NEUTRIK connector
Dimensions:	Length: 87,5 cm Depth: 14 cm Height: 18 cm
Weight:	9,45 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting