

## FUTURELIGHT POS-60 MK2 LED powerstick

Versatile LED color changing bar

Art. No.: 51841361

GTIN: 4026397331141



**The article is no longer in our assortment.**

### Description:

Much cry and little wool!

Big is relative. Mentally as well as anatomically. The same applies to the fact that our FUTURELIGHT POS-60 MK2 is pretty big. Compared to other light bars, the 175cm wide ones surely break the mold. But not only the measurements do impress and stand out from the crowd. The performance of this powerful instrument is impressive. 60 high power LEDs from Lumileds (20 x red, 20 x blue, 20 x green) provide a glistening bright light, producing strong and diverse colors which supply together with the implemented effects a convincing light show. Hereby it doesn't matter whether 6, 15, 60 or 63 DMX channels are dialed as the scope is substantial and more than sufficient. In comparison to the dip switch of its predecessor, the POS-20 MK2 is equipped with a display to regulate settings and to exchange lenses for generating the angle of radiation easily. A easy operation is given and the device stands its ground even on wide stages with moving heads and other spotlights.

### Features:

- 6, 15, 60 or 63 DMX channels selectable for numerous applications
- Equipped with 60 x 1 W LEDs: 20 x red, 20 x blue, 20 x green
- Different radiation angles possible via optional, exchangeable lens modules
- High power LEDs made by Lumileds, USA
- Long LED life
- Each LED can be controlled individually
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Stepless RGB color changing
- Programmable color change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Strobe effect with 1-18 flashes per second

### Logistic

EAN / GTIN: 4026397331141

Weight: 12,20 kg

Length: 1.78 m

Width: 0.28 m

Height: 0.16 m

Bulky product

- Programmed chaser
- 8 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- Rainbow effect with adjustable speed
- Addressing via control panel with 4-digit LED display
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via every standard DMX controller
- Feed-through output allows to power another device

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140,00 W
DMX channels:	6
Dimensions:	Length: 1,75 m Depth: 23 cm Height: 9 cm
DMX channels:	6/15/60/63
DMX connection:	3-pin XLR
Flash-rate:	18 Hz
LED number:	60
Dimensions (L x W x H):	1750 x 230 x 90 mm
Weight:	10.5 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting