

FUTURELIGHT DMH-90 LED Moving Head

High performance LED Moving Head with LUMINUS CBM-360 LED

Art. No.: 51841950 GTIN: 4026397461633











The article is no longer in our assortment.

Features:

- 1 extra bright LUMINUS CBM-360 LED for best luminance
- 16, 18 or 19 DMX channels selectable
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link

Logistic

EAN / GTIN: 4026397461633

Weight: 16,00 kg Length: 0.56 m Width: 0.43 m Heigth: 0.35 m

- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via any standard DMX controller
- Control via Sound to light via Microphone; DMX; RDM

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
Max. TILT movement:	270° Positioning
Max. PAN movement:	630° Positioning
Gobos:	Outside diameter 27mm
	Image diameter 22mm
DMX channels:	16; 18; 19
Control:	Sound to light via Microphone; DMX; RDM
Beam angle (1/2 peak):	14°
Color:	Black
Dimensions:	Width: 34,3 cm
	Depth: 25 cm
	Height: 42,8 cm
Weight:	13,70 kg
DMX channels:	16/18/19
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	LUMINUS CBM-360
LED number:	1
Beam angle:	14°
Color-wheel:	8 dichroic filters plus open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	343 x 250 x 428 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting