

FUTURELIGHT DMH-150 LED Moving Head

High performance LED moving head with 150 W COB LED

Art. No.: 51841970 GTIN: 4026397474534



The article is no longer in our assortment.

Features:

- Equipped with a 150 W COB LED comparable to a 575 W discharge lamp
- With integrated wireless receiver for WDMX operation (Wireless Solution made in Sweden)
- 21, 23 or 24 DMX channels selectable (up to software version 1.1.00)
- 14, 16, 21 or 24 DMX channels selectable (from software version 1.1.01)
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Gobo wheel 2 with 7 static gobos plus open
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Autofocus
- Steplessly adjustable iris
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset

Logistic

EAN / GTIN: 4026397474534 Weight: 16,15 kg Length: 0.52 m Width: 0.43 m Heigth: 0.36 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Control via sound to light via microphone; DMX; RDM
- Preprogrammed in Light Captain

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------------------|---|
| Power consumption: | 210 W |
| Max. TILT movement: | 270° positioning |
| Max. PAN movement: | 630° positioning |
| Gobos: | Outside diameter 27mm Image diameter 22mm |
| DMX channels: | 21 |
| Control: | Sound to light via microphone; DMX; RDM |
| Preprogrammed in: | Light Captain |
| Beam angle (1/2 peak): | 14° |
| Color: | Black |
| Dimensions: | Width: 34,3 cm Depth: 25 cm Height: 42,8 cm |
| Weight: | 14,10 kg |
| DMX channels: | 21/23/24 (up to software version 1.1.00) |
| DMX channels: | 14/16/21/24 (from software version 1.1.01) |
| DMX connection: | 3-pin XLR |
| Sound-control: | via built-in microphone |
| Wireless signal transmission: | 2.4 GHz (ISM) |
| LED type: | Array 150 W |
| LED number: | 1 |
| Beam angle: | 14° |
| Color-wheel: | 8 dichroic filters plus open |
| Static gobo-wheel: | 7 gobos and open |
| Rotating gobo-wheel: | 7 gobos and open |
| Outside diameter of the gobos: | 27 mm |
| Image diameter of the gobos: | 22 mm |
| Maximum PAN-movement: | 630° |
| Maximum TILT-movement: | 270° |
| Dimensions (L x W x H): | 343 x 250 x 428 mm |
| Special product: | Not designed for household room illumination |
| | |