

FUTURELIGHT LED CND Panel P37.5 90x90cm

Outdoor LED CND panel

Art. No.: 51843120

GTIN: 4026397400809



The article is no longer in our assortment.

Features:

- Modular LED video panel for outdoor use, IP44
- Extra bright and colorful projection of videos, animations and graphics
- Ideal for rental companies, stage/fair construction and fixed installation
- Modular display concept allows the build-up of large areas
- 37.5 mm pixel pitch (seamless image at about 30 m)
- 3300 nits bright
- 24 x 24 pixels
- Transparent design in ultra-light and thin aluminum version
- Integrated suspension supports for fast and easy setup
- Low-noise operation due to fanless cooling concept
- Ethernet-based signal distribution, PowerCon inputs and outputs
- Receiving module already integrated - only the optional PCI sending card and PC software LED studio is needed (item 51843170)
- Recommended media software: MADRIX dvi
- Comes with XLR connection cables and power cables

Logistic

EAN / GTIN: 4026397400809

Technical specifications:

Power consumption: 180,00 W

IP classification: IP44

Dimensions: Width: 90 cm
Depth: 9,5 cm
Height: 90 cm

Weight:	14 kg
Power supply:	200-264 V AC, 50/60 Hz
Resolution:	24 x 24 pixels
Pixel pitch:	37.5 mm
Pixel density:	712/m ²
Pixel configuration:	DIP546 RGB
Lifetime:	approx. 50000 hours
Display port:	DVI/RJ45
Display mode:	synchronous to video source
Drive mode:	static
Screen resolution:	rec. 1024 x 768, max. 1280 x 1024
Brightness:	>3300 cd/m ² (nits)
Viewing angle:	145° horizontally, 110° vertically
Best viewing distance:	30 to 200 m
Frame rate:	60 Hz
Data refresh rate:	600 Hz
Colors:	16.7 million (R 256, G 256, B 256)
Protection grade:	IP44
Operating temperature:	-10 to 50 °C
Humidity:	up to 950 %
Dimensions (L x W x H):	95 x 900 x 900 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting