

## EUROLITE PVS/SVS Video processor

Video processor for PVS and SVS LED displays

Art. No.: 51843273

GTIN: 4026397468410



**The article is no longer in our assortment.**

### Features:

- High-resolution video processor with built-in sending card for use with PVS and SVS LED displays
- Delivers excellent image results from all signal sources for the LED displays
- Required as an alternative to the PCI sending card, for use of other video signals than DVI or HDMI - in particular live show playback
- Extensive connection options allow the use of all conceivable image sources: e.g. PC, HD-DVD or Blu Ray, set-top boxes, game consoles
- Processor-based image enhancement stabilizes, denoises and digitizes the signal
- Inputs: 3 x Composite, 1 x S-Video, 1 x VGA D-Sub, 1 x DVI, 2 x HDMI
- Outputs: 1 x DVI, 1 x VGA
- PC interfaces for configuration and real-time control: USB, Ethernet (TCP/IP) and RS-232
- Supports full HD 1080p
- Supports user-defined resolutions up to 2048 x 1280 pixels
- Supports keyboard operation
- PIP - Picture-in-picture
- Image crop and zoom
- Image freeze
- Multiple presets
- Rack installation with 1 unit
- (19") 48.3 cm rack installation

### Logistic

EAN / GTIN: 4026397468410

Weight: 4,70 kg

Length: 0.62 m

Width: 0.33 m

Height: 0.30 m

### Technical specifications:

Housing design: (19") 48.3 cm rack installation

Dimensions:	Width: 48,3 cm Depth: 30 cm Height: 4,45 cm
Power supply:	85-264 V AC, 50/60 Hz/2 A
Inputs:	
Audio:	5 x stereo RCA
Digital:	3 x Composite, 1 x S-Video, 1 x VGA D-Sub, 1 x DVI, 2 x HDMI
Standards:	PAL, NTSC
Outputs:	
Audio:	6.3 mm jack
Digital:	1 x VGA D-Sub, 1 x DVI-I
Resolutions:	800 x 600 x 60 Hz bis 2048 x 1280 x 60 Hz
Control:	
Front panel:	LED display, backlit push buttons
Communication:	LAN (TCP/IP), RS-232, USB
Dimensions (L x W x H):	482 x 300 x 45 mm (19", 1 U)
Weight:	2.5 kg