

## EUROLITE LED FLD-144 UV 10mm Flood

LED UV floodlight, incl. IR remote control

Art. No.: 51913861

GTIN: 4026397647617



**The article is no longer in our assortment.**

### Features:

- 144 x 10 mm UV LED for dynamic strobe effects and blacklight
- Built-in auto and music show programs
- UV, dimmer and strobe effects
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Supports QuickDMX - the wireless DMX system from Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Swivel mounting bracket
- Additional bracket for floor use
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 144 powerful LEDs 10 mm ultra violet (UV)
- UV effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; LED PC-Control 512
- With a beam angle of 20°

### Package contents

- 1 x remote control

### Logistic

EAN / GTIN: 4026397647617

Weight: 2,70 kg

Length: 0.36 m

Width: 0.13 m

Height: 0.27 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	17 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	144 x 10 mm ultra violet (UV)
DMX channels:	1; 2; 2; 3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; LED PC-Control 512
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	35°
Housing color:	Black
Dimensions:	Width: 34,5 cm Depth: 8,5 cm Height: 22 cm
Weight:	2,40 kg
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting