

## EUROLITE LED CLS-9 QCL RGB/WW 9x7W

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

Art. No.: 51913901

GTIN: 4026397712841



**List price: 272.51 €**

incl. 19% VAT.

### Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 3 buttons on the remote control for saving your own settings
- 9 powerful LEDs 7 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Master/slave function; Sound to light via Microphone; IR remote control
- Flicker-free
- With a beam angle of 10°
- With Mounting bracket
- OLED display
- Silent operation
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; Stage; theater; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

### Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x diffusor cover, 1 x remote control, 1 x barndoor, 2 x knurled screw

### Logistic

EAN / GTIN: 4026397712841

Weight: 3,50 kg

Length: 0.30 m

Width: 0.19 m

Height: 0.24 m

## Technical specifications:

|                         |                                                                                                                                                                                      |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                               |
| Power consumption:      | 54 W                                                                                                                                                                                 |
| IP classification:      | IP20                                                                                                                                                                                 |
| Protection class:       | Protection class I                                                                                                                                                                   |
| Power connection:       | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)                                                                                         |
| Power output:           | 1 x PowerCON (gray)                                                                                                                                                                  |
| Lamp type:              | LED lamp                                                                                                                                                                             |
| LED:                    | 9 x 7 W 4in1 QCL RGB/WW (homogenous color mix)                                                                                                                                       |
| Flash rate:             | 1 - 23 Hz                                                                                                                                                                            |
| DMX channels:           | 3; 4; 6; 8; 11                                                                                                                                                                       |
| DMX input:              | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version                                                                                                             |
| DMX output:             | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version                                                                                                             |
| Cooling:                | Passive convection cooling                                                                                                                                                           |
| Control:                | Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Master/slave function; Sound to light via Microphone; IR remote control |
| Preprogrammed in:       | Light Captain; EASY SHOW 2; EASY SHOW 3                                                                                                                                              |
| Projection:             | Flicker-free                                                                                                                                                                         |
| Beam angle:             | 10°                                                                                                                                                                                  |
| Beam angle (1/2 peak):  | 10°<br>Frost filter 18°                                                                                                                                                              |
| Beam angle (1/10 peak): | 28°<br>Frost filter 47°                                                                                                                                                              |
| Housing color:          | Black                                                                                                                                                                                |
| Attachment system:      | Mounting bracket                                                                                                                                                                     |
| Display type:           | OLED display                                                                                                                                                                         |
| Dimensions:             | Length: 27,1 cm<br>Width: 14,3 cm<br>Height: 21,3 cm                                                                                                                                 |
| Weight:                 | 3,20 kg                                                                                                                                                                              |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                                                            |
| Remote control          |                                                                                                                                                                                      |
| Battery:                | 1 x Button cell 3.0 V CR2032 lithium manganese built-in                                                                                                                              |
| Legal specifications    |                                                                                                                                                                                      |
| Special product:        | Not designed for household room illumination                                                                                                                                         |
| Intended use:           | Show effect lighting                                                                                                                                                                 |