

## EUROLITE LED PAR-64 HCL 12x10W Floor sil

PAR spot with 12 x 10 W 6in1 LED in R, G, B, A, W, UV

Art. No.: 51914026

GTIN: 4026397576597



### Features:

- Stand-alone or DMX mode
- Stepless color blend, color change, dimmer, strobe effect and UV effect
- Equipped with 12 x 10 W LEDs in red, green, blue, amber, white and UV
- Designed for hanging or standing installation
- Swivel mounting bracket
- Control panel with LED display for easy configuration
- Convenient wireless control via included IR remote control
- Mains input and output for power linking up to 8 units
- Available in silver or black
- 12 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- With a beam angle of 33°

### Logistic

EAN / GTIN: 4026397576597

Weight: 3,25 kg

Length: 0.25 m

Width: 0.26 m

Height: 0.39 m

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp

LED type:	12 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	4; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Beam angle (1/2 peak):	33°
Housing color:	Silver
Dimensions:	Width: 29.6 cm Depth: 27.7 cm Height: 37.5 cm
Weight:	2.85 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

---

**Scope of delivery:**

1 x remote control