

EUROLITE LED PAR-64 HCL 12x10W Floor bk

PAR spot with 12 x 10 W 6in1 LED in R, G, B, A, W, UV

Art. No.: 51914027

GTIN: 4026397576610



List price: 296.31 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect; UV effect
- Control via stand-alone; DMX; Sound to light via Microphone; IR remote control
- With a beam angle of 33°
- With double bracket
- The device is cooled by temperature-controlled fan
- Preprogrammed in Light´J; LED PC-Control 512; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x6; Light Captain
- 3 integrated show programs
- Direct color selection for 15 preset colors
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397576610

Weight: 3,40 kg

Length: 0.25 m

Width: 0.26 m

Height: 0.39 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 125 W

IP classification: IP20

| | |
|-------------------------|--|
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED: | 12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) |
| DMX channels: | 4; 10 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX; Sound to light via Microphone; IR remote control |
| Preprogrammed in: | Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x6; Light Captain |
| Beam angle: | 33° |
| Beam angle (1/2 peak): | 33° |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 29,6 cm Depth: 27,7 cm Height: 37,5 cm |
| Weight: | 2,80 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |