

## EUROLITE LED PAR-64 QCL 12x8W floor bl

PAR spot with 12 x 8 W 4in1 LED and RGBW color mixing

Art. No.: 51914030

GTIN: 4026397613827



**The article is no longer in our assortment.**

### Description:

PAR spotlight with RGBW color mixing incl. remote control

The Eurolite LED PAR-64 is equipped with 12 powerful RGBW-LEDs (4in1) of 8 Watt each. You can use it on stage, in the club lighting area or as a floor spot, thanks to its additional bracket for placement.

The color temperature of the white tone is adjustable in six steps, the RGBW color mixing is stepless. 24 colors can be selected directly. The spotlight has a dimmer and strobe effect.

The effect spot can be controlled via DMX, standalone or via music control via the built-in microphone with adjustable microphone sensitivity. In auto and music mode you can play the integrated show programs.

Addressing and settings are possible via a control unit with four-digit LED display. Up to eight devices can be easily interconnected using the existing IEC mains connections.

The Eurolite LED PAR-64 can be easily remote controlled with the supplied infrared remote control.

### Features:

- Stepless color blend, color change, color fade, dimmer and strobe effect
- Mains input and output for power linking up to 8 units
- 12 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- Integrated show programs
- Direct color selection for 24 preset colors
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function

### Logistic

EAN / GTIN: 4026397613827

Weight: 3,11 kg

Length: 0.26 m

Width: 0.26 m

Height: 0.34 m

- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
  - Flicker-free
  - With a beam angle of 14°
  - With double bracket
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

## Technical specifications:

|                         |   |
|-------------------------|---|
| Power supply:           | 100-240 V AC, 50/60 Hz  |
| Power consumption:      | 70 W  |
| IP classification:      | IP20  |
| Protection class:       | Protection class I  |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                |
| Power output:           | 1 x IEC connector (F) mounting version  |
| Lamp type:              | LED lamp  |
| LED:                    | 12 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  |
| DMX channels:           | 2; 3; 4; 5; 6; 9  |
| DMX input:              | 1 x 3-pin XLR (M) mounting version  |
| DMX output:             | 1 x 3-pin XLR (F) mounting version  |
| Control:                | Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function                                       |
| Preprogrammed in:       | Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Projection:             | Flicker-free  |
| Beam angle:             | 14°   |
| Beam angle (1/2 peak):  | 14°   |
| Beam angle (1/10 peak): | 29°   |
| Housing color:          | Black   |
| Attachment system:      | Double bracket  |
| Dimensions:             | Width: 29,6 cm<br>Depth: 27,3 cm<br>Height: 34 cm   |
| Weight:                 | 2,70 kg   |
| Remote control          |   |
| Battery:                | 1 x Button cell 3.0 V CR2025 lithium manganese built-in   |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination  |
| Intended use:           | Show effect lighting  |