

EUROLITE LED IP T-PIX 8 QCL Bar

Weather-proof (IP65) bar with RGBW color mixing and segment control

Art. No.: 51914116

GTIN: 4026397674965



Features:

- DMX and power terminals intelligently designed for easy wiring
- 384 LEDs 0.4 W SMD 5050 4in1 RGBW (homogenous color mix)
8 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response
- Strobe effect
- Direct color selection for 32 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 120°
- With mounting bracket; with omega bracket
- Suitable for outdoor use
- Silent operation

Logistic

EAN / GTIN: 4026397674965

Weight: 9,15 kg

Length: 1.08 m

Width: 0.19 m

Height: 0.26 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version

Lamp type:	LED lamp
LED type:	384 x 0.4 W SMD 5050 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 25 Hz
DMX channels:	4; 9; 16; 37
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	2x mounting bracket Omega bracket
Dimensions:	Length: 99.0 cm Depth: 16.0 cm Height: 14.0 cm
Weight:	8.20 kg
Noise classification:	Class 0 (no noise at all)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x XLR cable
2 x omega bracket