

EUROLITE LED IP PAR 14x10W HCL

Weather-proof (IP65) spotlight with 6in1 HCL RGBWA/UV color mixing and frost filters

Art. No.: 51914172

GTIN: 4026397670233



Features:

- 14 LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Fixtures available for Light J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397670233

Weight: 8,10 kg

Length: 0.41 m

Width: 0.36 m

Height: 0.35 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 95 W

IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	14 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	3; 5; 6; 8; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Fixtures available for:	Light´ J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´ J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 31 cm Depth: 22.5 cm Height: 36.5 cm
Weight:	6.80 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Material:	Plastic, 2 mm
Dimensions:	Diameter: Ø 20.5 cm
Cable length:	Approx. 1.5 m
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
3 x frost filter
1 x XLR cable
2 x knurled screw
1 x user manual