

### **EUROLITE LED IP PAR 14x8W QCL**

Weather-proof (IP65) spotlight with 4in1 QCL RGBW color mixing and diffuser discs

Art. No.: 51914178 GTIN: 4026397645217











List price: 415.31 €

incl. 19% VAT.

## Features:

- 14 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- With a beam angle of 15°
- With double bracket
- Monochrome LCD display
- Suitable for outdoor use IP65
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Installation; Stage; Rental; architecture
- Application possibility: Standing; suspended; on stand

#### Package contents

 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 3 x diffusor cover, 1 x xLR cable, 2 x knurled screw

## Logistic

EAN / GTIN: 4026397645217

Weight: 8,33 kg Length: 0.41 m Width: 0.36 m Heigth: 0.35 m

# **Technical specifications:**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	14 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 4; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	15°
Beam angle (1/2 peak):	15°
	27° 30° 60°
Beam angle (1/10 peak):	
Beam angle (1/10 peak):  Housing color:	30° 60°
Housing color:	30° 60° 32°
	30° 60° 32° Black
Housing color: Attachment system:	30° 60° 32° Black Double bracket
Housing color: Attachment system: Display type:	30° 60° 32° Black Double bracket Monochrome LCD display Width: 31 cm Depth: 22,5 cm
Housing color: Attachment system: Display type: Dimensions:	30° 60° 32° Black Double bracket Monochrome LCD display Width: 31 cm Depth: 22,5 cm Height: 36,5 cm
Housing color:  Attachment system:  Display type:  Dimensions:  Weight:	30° 60° 32° Black Double bracket Monochrome LCD display Width: 31 cm Depth: 22,5 cm Height: 36,5 cm 7,15 kg
Housing color:  Attachment system:  Display type:  Dimensions:  Weight:  Noise classification:	30° 60° 32° Black Double bracket Monochrome LCD display Width: 31 cm Depth: 22,5 cm Height: 36,5 cm 7,15 kg Class 0 (no noise at all)
Housing color:  Attachment system:  Display type:  Dimensions:  Weight:  Noise classification:  Photobiological safety:	30° 60° 32° Black Double bracket Monochrome LCD display Width: 31 cm Depth: 22,5 cm Height: 36,5 cm 7,15 kg Class 0 (no noise at all)
Housing color:  Attachment system:  Display type:  Dimensions:  Weight:  Noise classification:  Photobiological safety:  Remote control	30° 60° 32° Black Double bracket Monochrome LCD display Width: 31 cm Depth: 22,5 cm Height: 36,5 cm 7,15 kg Class 0 (no noise at all) Risk Group 0  1 x Button cell 3.0 V CR2025 lithium manganese
Housing color:  Attachment system:  Display type:  Dimensions:  Weight:  Noise classification:  Photobiological safety:  Remote control  Battery:	30° 60° 32° Black Double bracket Monochrome LCD display Width: 31 cm Depth: 22,5 cm Height: 36,5 cm 7,15 kg Class 0 (no noise at all) Risk Group 0  1 x Button cell 3.0 V CR2025 lithium manganese