

EUROLITE LED IP PAR 3x12W HCL

Compact, weather-proof DMX spot (IP65) with 3 x 12 W 6in1 LED (RGBWA+UV)

Art. No.: 51914188

GTIN: 4026397558012



The article is no longer in our assortment.

Features:

- Equipped with 3 high-power 12 W 6in1 LEDs in the colors red, green, blue, amber, white and UV
- For architectural lighting
- Suitable for external use (IP65)
- Stepless RGBAW+UV color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Power terminals for power linking up to 8 units
- 3 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by passive convection cooling
- Control via DMX
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
- Flicker-free
- With a beam angle of 20°
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397558012
Weight: 2,90 kg
Length: 0.26 m
Width: 0.21 m
Height: 0.21 m

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 2 x adapter cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED:	3 x 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	4; 5; 6; 9; 12; 7
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	DMX
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	40°
Housing color:	Black
Dimensions:	Width: 18,1 cm Depth: 10,2 cm Height: 20,6 cm
Weight:	2,57 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting