

EUROLITE LED IP PAR 3x12W HCL

Compact, weather-proof DMX spot (IP65) with 3 x 12 W 6in1 LED (RGBWA+UV)

Art. No.: 51914188 GTIN: 4026397558012









The article is no longer in our assortment.

Features:

- Equipped with 3 high-power 12 W 6in1 LEDs in the colors red, green, blue, amber, white and
- For architectural lighting
- Suitable for external use (IP65)
- Stepless RGBAW+UV color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Power terminals for power linking up to 8 units
- 3 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by passive convection cooling
- Control via DMX
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain
- Flicker-free
- With a beam angle of 20°
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397558012

Weight: 2,90 kg Length: 0.26 m Width: 0.21 m Heigth: 0.21 m

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 2 x adapter cable

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|-------------------------|---|
| Power consumption: | 30 W |
| IP classification: | IP65 |
| Power connection: | Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided) |
| Power output: | 1 x 3-pin screw plug connector (F) IP |
| Lamp type: | LED lamp |
| LED type: | 3 x 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) |
| Flash rate: | 0 - 18 Hz |
| DMX channels: | 4; 5; 6; 9; 12; 7 |
| DMX input: | 1 x 3-pin screw plug connector (M) IP |
| DMX output: | 1 x 3-pin screw plug connector (F) IP |
| Cooling: | Passive convection cooling |
| Control: | DMX |
| Preprogrammed in: | Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 20° |
| Beam angle (1/2 peak): | 20° |
| Beam angle (1/10 peak): | 40° |
| Housing color: | Black |
| Dimensions: | Width: 18,1 cm |
| | Depth: 10,2 cm |
| | Height: 20,6 cm |
| Weight: | 2,57 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |