

EUROLITE LED IP PAR 12x8W QCL Spot

Weather-proof (IP65) spotlight with 12 x 8 W LED and 4in1 QCL RGBW color mixing

Art. No.: 51914231

GTIN: 4026397672114



List price: 355.81 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 8 W 4in1 QCL RGBW (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Strobe effect
 - Direct color selection for 25 preset colors
 - The device is cooled by passive convection cooling
 - Control via DMX; IR remote control; stand-alone
 - Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
 - Flicker-free
 - With a beam angle of 15°
 - With double bracket
 - LCD display
 - Mains input and output for power linking up to 8 units
 - Suitable for outdoor use IP65
 - With pressure compensation membrane
 - Silent operation
 - For application areas such as: Installation; stage; rental; architecture
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397672114

Weight: 5,75 kg

Length: 0.35 m

Width: 0.32 m

Height: 0.20 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Fuse:	T 5 A fuse fix on board
Lamp type:	LED lamp
LED type:	12 x 8 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0,5 - 24 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	5900 Hz
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 28,5 cm Depth: 15,3 cm Height: 31,35 cm
Weight:	5,20 kg
Noise classification:	Class 0 (no noise at all); Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2,5 mm
Power cord	
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,2 m
Remote control	

Battery:	1 x button cell 3.0 V CR2025 lithium manganese
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting