

# **EUROLITE LED IP PAR 3x9W SCL spot**

Weather-proof (IP65) spotlight with 3 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

**Art. No.: 51914235** GTIN: 4026397683981











**List price: 260.61 €** 

incl. 19% VAT.

# Features:

- 3 powerful LEDs 9 W 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Preprogrammed in Light'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Installation; Stage; Rental; architecture
- Application possibility: On stand; suspended

#### Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### **Technical specifications:**

| Power supply:      | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 35 W                   |
| IP classification: | IP65                   |
| Protection class:  | Protection class I     |

## Logistic

EAN / GTIN: 4026397683981

Weight: 3,20 kg Length: 0.19 m Width: 0.19 m Heigth: 0.29 m

| Power connection:       | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
|-------------------------|---------------------------------------------------------------------------------------------|
| Power output:           | IP T-Con (F) mounting version                                                               |
| LED:                    | 3 x 9 W 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)                                      |
| Flash rate:             | 0 - 20 Hz                                                                                   |
| DMX channels:           | 3; 5; 7; 9; 13                                                                              |
| DMX input:              | 3-pin XLR (M) mounting version IP                                                           |
| DMX output:             | 3-pin XLR (F) mounting version IP                                                           |
| Cooling:                | Passive convection cooling                                                                  |
| Control:                | Stand-alone; IR remote control; DMX                                                         |
| Preprogrammed in:       | Light'J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3                               |
| Projection:             | Flicker-free                                                                                |
| Beam angle:             | 15°                                                                                         |
| Beam angle (1/2 peak):  | 15°                                                                                         |
| Beam angle (1/10 peak): | 30°                                                                                         |
| Housing color:          | Black                                                                                       |
| Attachment system:      | Double bracket                                                                              |
| Display type:           | LCD display                                                                                 |
| Dimensions:             | Width: 21,5 cm<br>Depth: 17,1 cm<br>Height: 24,4 cm                                         |
| Weight:                 | 3,00 kg                                                                                     |
| Noise classification:   | Class 0 (no noise at all)                                                                   |
| Photobiological safety: | Risk Group 0                                                                                |
| Remote control          |                                                                                             |
| Battery:                | 1 x Button cell 3.0 V CR2025 lithium manganese built-in                                     |
| Legal specifications    |                                                                                             |
| Special product:        | Not designed for household room illumination                                                |
| Intended use:           | Show effect lighting                                                                        |