

## EUROLITE LED IP Tourlight 200 RGB+WW

Silent IP65 spotlight with RGB+WW color mixture, QuickDMX, CRI >90

Art. No.: 51914252

GTIN: 4026397705072



**List price: 534.31 €**

incl. 19% VAT.

### Features:

- Integrated QuickDMX transceiver for wireless DMX control
  - 1 powerful LED 200 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
  - 9 integrated show programs
  - Direct color selection for 27 preset colors
  - The device is cooled by passive convection cooling
  - Control via stand-alone; DMX; QuickDMX; IR remote control; Master/slave function
  - Flicker-free
  - With a beam angle of 30°
  - Very high color rendering index (CRI)
  - With Mounting bracket; with Omega bracket; with bracket for floor use
  - LCD display
  - Suitable for outdoor use IP65
  - For application areas such as: Installation; Stage; theater; Rental; architecture
  - Dimmer electronic; color blend stepless
  - Preprogrammed in Light Captain; Light J
  - Mains input and output for power linking up to 8 units
  - Silent operation
  - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x remote control, 1 x battery

### Logistic

EAN / GTIN: 4026397705072

Weight: 5,50 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.39 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	105 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	1 x 200 W COB (chip-on-board) 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; IR remote control; Master/slave function
Preprogrammed in:	Light Captain; Light J
Projection:	Flicker-free
Beam angle:	30°
Beam angle (1/2 peak):	30°
Beam angle (1/10 peak):	60°
Color rendering index (CRI):	96 Ra
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket Bracket for floor use
Display type:	LCD display
Dimensions:	Width: 25,1 cm Depth: 27,2 cm Height: 32,7 cm Diameter: Ø 18,2 cm
Weight:	4,50 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting