#### Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

# eurolite

### EUROLITE LED IP FL-50 COB RGB 120° RC

Outdoor floodlight (IP65) with 50 W COB LED (RGB) and IR remote control

Art. No.: 51914610

## GTIN: 4026397455458

List price: 106.98 € incl. 19% VAT.

### Features:

- Add highlights to your house and garden
- Compact design
- 1 powerful LED 50 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable
- Strobe effect
- Direct color selection for 16 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control
- With a beam angle of 120°
- With mounting bracket
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; party room; small rental
- Application possibility: Suspended Package contents
- 1 x spotlight, 1 x remote control, 1 x user manual

#### **Technical specifications:**

Power supply:	230 V AC, 50 Hz
Power consumption:	50 W
IP classification:	IP65
Protection class:	Protection class I

### Logistic

EAN / GTIN: 4026397455458 Weight: 2,15 kg Length: 0.29 m Width: 0.25 m Heigth: 0.17 m











Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm <sup>2</sup> H05RN-F
Cable length:	Approx. 1,6 m
Lamp type:	LED lamp
LED type:	1 x 50 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color of light:	Switching colors
Housing color:	Silvergrey
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 28,5 cm Depth: 14,5 cm Height: 23,5 cm
Weight:	2,00 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Mounting bracket	
Diameter mounting holes:	3 x Ø10mm
Material:	Metal, 1,5 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting