

EUROLITE LED IP FL-50 COB RGB 60° RC

Brilliant COB outdoor floodlight (IP65) with LED technology

Art. No.: 51914618

GTIN: 4026397552744



The article is no longer in our assortment.

Features:

- Add highlights to your house and garden
- Ideal LED luminaire for indoor or outdoor use
- The weather-resistant housing also allows operation during bad weather
- For permanent installation, mounting bracket included
- Extremely compact housing in an appealing design
- Equipped with 1 COB RGB LED
- Beam reflection angle of 60°
- Ready for connection via power cord with safety-plug
- IR-remote control with an operation range of approximately 7 m included in delivery
- Automatic color change or manual program or color selection
- Built-in programs for color change and color fade
- Adjustable program speed and brightness
- Direct color selection for 15 preset colors + white
- Memory function for control programs via the Flash, Strobe, Fade and Smooth buttons of the IR remote control
- 1 powerful LED 50 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control
- With a beam angle of 60°
- Suitable for outdoor use IP65

Package contents

- 1 x spotlight, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397552744

Weight: 2,90 kg

Length: 0.28 m

Width: 0.25 m

Height: 0.17 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP65
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 1,7 m
Lamp type:	LED lamp
LED:	1 x 50 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control
Beam angle:	60°
Beam angle (1/2 peak):	60°
Housing color:	Black
Color:	Clear
Dimensions:	Width: 28,2 cm Depth: 23,3 cm Height: 14 cm
Weight:	2,70 kg
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Protction grade:	IP65
LED-Typ:	COB, RGB
LED number:	1
Beam angle:	60°
Maximum remote control range:	7 m
Dimensions (L x W x H):	140 x 282 x 233 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting