

## EUROLITE LED SLS-3 Hybrid Floor

Flat spotlight with 3 x 4 W 4in1 LED (RGB+UV) + 18 strobe LEDs

Art. No.: 51915274

GTIN: 4026397617764



**The article is no longer in our assortment.**

### Features:

- 3 high-power 4 W 4in1 LEDs for RGB color mixing and blacklight
- 18 cold white 0.5 W LEDs for dynamic strobe effects
- Auto, music, master/slave and DMX mode
- 4 built-in auto and music show programs
- Direct color selection for 18 preset colors
- Individual control of all RGB+UV and strobe LEDs for use as blacklight, stroboscope or PAR spotlight
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Sound-control via built-in microphone with adjustable microphone sensitivity
- DMX512 control possible via any commercial DMX controller
- 2, 3, 5 or 10 DMX channels selectable
- Flat housing form requires minimal space when rigging
- Swivel mounting bracket
- Additional bracket for floor use
- Feed-through output allows to power up to 8 devices
- 18 powerful LEDs 0,5 W SMD 5050 cold white (CW)
- 3 powerful LEDs 4 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Strobe effect
- Control via stand-alone; DMX; IR remote control
- Preprogrammed in LED PC-Control 512
- With a beam angle of 12°

### Package contents

- 1 x remote control

### Logistic

EAN / GTIN: 4026397617764

Weight: 1,56 kg

Length: 0.27 m

Width: 0.23 m

Height: 0.16 m

## Technical specifications:

|                         |  |
|-------------------------|--|
| Power supply:           | 100-240 V AC, 50/60 Hz   |
| Power consumption:      | 20 W   |
| IP classification:      | IP20   |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:           | 1 x IEC connector (F) mounting version   |
| Lamp type:              | LED lamp   |
| LED:                    | 18 x 0,5 W SMD 5050 cold white (CW)<br>3 x 4 W high-power 4in1 QCL RGB/UV (homogenous color mix) |
| DMX channels:           | 2; 3; 5; 10  |
| Control:                | Stand-alone; DMX; IR remote control  |
| Preprogrammed in:       | LED PC-Control 512   |
| Beam angle:             | 12°  |
| Beam angle (1/2 peak):  | 12°  |
| Beam angle (1/10 peak): | 26°  |
| Housing color:          | Black  |
| Dimensions:             | Width: 21 cm<br>Depth: 12,5 cm<br>Height: 24,5 cm  |
| Weight:                 | 1,29 kg  |
| Photobiological safety: | Risk Group 0   |
| Remote control          |  |
| Battery:                | 1 x Button cell 3.0 V CR2025 lithium manganese built-in  |
| DMX channels:           | 2/3/5/10   |
| DMX connection:         | 3-pin XLR  |
| Sound-control:          | via built in microphone  |
| LED type:               | 3 x 4 W RGB+UV (4in1), 18 x 0.5 W cold white   |
| Flash rate:             | 0-20 Hz  |
| Beam angle:             | 12°  |
| Dimensions (L x W x H): | 125 x 210 x 245 mm   |
| Legal specifications    |  |
| Special product:        | Not designed for household room illumination   |
| Intended use:           | Show effect lighting   |