

## EUROLITE LED SLS-3 Hybrid Floor

Flat spotlight with 3 x 4 W 4in1 LED (RGB+UV) + 18 strobe LEDs

Art. No.: 51915274

GTIN: 4026397617764



**The article is no longer in our assortment.**

### Features:

- 3 high-power 4 W 4in1 LEDs for RGB color mixing and blacklight
- 18 cold white 0.5 W LEDs for dynamic strobe effects
- Auto, music, master/slave and DMX mode
- 4 built-in auto and music show programs
- Direct color selection for 18 preset colors
- Individual control of all RGB+UV and strobe LEDs for use as blacklight, stroboscope or PAR spotlight
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Sound-control via built-in microphone with adjustable microphone sensitivity
- DMX512 control possible via any commercial DMX controller
- 2, 3, 5 or 10 DMX channels selectable
- Flat housing form requires minimal space when rigging
- Swivel mounting bracket
- Additional bracket for floor use
- Feed-through output allows to power up to 8 devices
- 18 LEDs 0.5 W SMD 5050 cold white (CW)
- 3 LEDs 4 W high-power 4in1 RGB/UV (homogenous color mix)
- Strobe effect
- Control via stand-alone; DMX; IR remote control
- With a beam angle of 12°

### Logistic

EAN / GTIN: 4026397617764

Weight: 1,56 kg

Length: 0.27 m

Width: 0.23 m

Height: 0.16 m

## Technical specifications:

---

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	18 x 0.5 W SMD 5050 cold white (CW) 3 x 4 W high-power 4in1 RGB/UV (homogenous color mix)
DMX channels:	2; 3; 5; 10
Control:	Stand-alone; DMX; IR remote control
Fixtures available for:	LED PC-Control 512
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	26°
Housing color:	Black
Dimensions:	Width: 21 cm Depth: 12.5 cm Height: 24.5 cm
Weight:	1.29 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
DMX channels:	2/3/5/10
DMX connection:	3-pin XLR
Sound-control:	via built in microphone
LED type:	3 x 4 W RGB+UV (4in1), 18 x 0.5 W cold white
Flash rate:	0-20 Hz
Beam angle:	12°
Dimensions (L x W x H):	125 x 210 x 245 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

---

1 x remote control