

## EUROLITE LED SLS-30 COB QCL Floor

LED floor spot with RGBW color mixing, incl. IR remote control

Art. No.: 51915301

GTIN: 4026397669268



**List price: 117.81 €**

incl. 19% VAT.

### Features:

- DMX and power terminals intelligently designed for easy wiring
- 1 powerful LED 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Multi beam effect; Strobe effect
- 5 integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via IR remote control; DMX; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 18°
- With double bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light'J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397669268

Weight: 1,33 kg

Length: 0.19 m

Width: 0.19 m

Height: 0.24 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	IR remote control; DMX; stand-alone; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	65°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Width: 21,5 cm Depth: 12,7 cm Height: 22,85 cm
Weight:	1,10 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	

Diameter mounting holes:	1 x Ø11mm; 2 x Ø10mm
Material:	Metal, 1,5 mm
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting