

EUROLITE LED Silent Par 12x10W RGBL

Fanless spot with RGBL color mixing and standing bracket

Art. No.: 51915345

GTIN: 4026397757217



Description:

This fixture offers a range of special features. Its color mixing based on red, green, blue, and lime allows not only for vibrant, punchy colors but also for subtle pastel tones, as well as high-quality yellow and orange shades. It can even produce convincing white light.

Thanks to its fanless design, the fixture operates completely silently. It is also highly versatile in terms of mounting: the bracket allows for both hanging and standing use, but can also be removed entirely if needed.

Its design also allows the fixture to be placed directly on its back, making it suitable for use as an uplight. An extendable stand foot enables precise angle adjustment. The side-mounted connectors ensure clean and flexible installation.

Features:

- 12 LEDs 10 W SMD 5050 4in1 RGBL (homogenous color mix)
- With a beam angle of 15°
- Good color rendering index (CRI)
- Silent operation
- Spot effect; uplight effect
- Direct color selection for 255 preset colors
- Control via DMX; stand-alone; sound to light via microphone; master/slave function; RDM; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
- With bracket for floor use; with mounting bracket
- Rubber feet
- Direct color temperature selection for 15 preset values
- Variable color temperature 1800 K - 12000 K

Logistic

EAN / GTIN: 4026397757217

Weight: 2,55 kg

Length: 0.32 m

Width: 0.28 m

Height: 0.21 m

- 22 integrated show programs
- Color change adjustable speed; color fade adjustable speed; color blend stepless; Dimmer electronic
- Mains input and output for power linking up to 8 units
- The device is cooled by passive convection cooling
- For application areas such as: Party room; mobile djs / entertainer; clubs/dancing school; stage
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1 mm ² H05VV-F
Power output:	1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, F 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 10 W SMD 5050 4in1 RGBL (homogenous color mix)
Flash rate:	2 - 20 Hz
DMX channels:	4; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version Bypass
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; master/slave function; RDM; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
Fixtures available for:	Light J; Light Captain
DMX features:	RDM For bidirectional communication over the DMX line
DMX fail mode:	Blackout
Beam angle:	15°
Beam angle (1/2 peak):	Spot 15° multicolor
Beam angle (1/10 peak):	30°
Color temperature:	1800K - 12000K adjustable
Color rendering index (CRI):	81 Ra
Housing color:	Black matte
Attachment system:	Bracket for floor use Mounting bracket
Display type:	4 digit 7-segment LED display
USB port:	1 x type A
Transport aid:	Rubber feet
Dimensions:	Width: 26.4 cm Depth: 14.12 cm Height: 27.15 cm

Weight:	2.20 kg
Noise classification:	Class 0 (no noise at all)
Material:	Plastic
Diameter mounting holes:	2 x Ø8.2mm
Material:	Metal, painted
Battery:	1 x button cell 3.0 V CR2025 lithium manganese
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x light effect
- 1 x mounting bracket
- 2 x screw
- 2 x washer
- 1 x user manual
- 1 x power cord
- 1 x battery
- 1 x remote control