

EUROLITE LED SLS-400 RGB 10mm Floor

Slimline LED spot with 180 x 10 mm LED

Art. No.: 51915350

GTIN: 4026397382822



Description:

It is the popular KLS which has paved the path for Slim Line Spots. The KLS was the first successful attempt to replace bulky PAR spots by compact and flat ones - on a bar with 4 spots next to another. As is well known, the concept has been a raving success. As a logic consequence we also transformed the form of single spots - the SLS were born.

Obvious advantages of the SLS: they are slim. Compared to common PAR spots they considerably save space. For this reason they are much more flexible and handy. This is also true for installation, stock ground and transport - for most SLS we sell special cases which are smaller and cheaper than those for PAR spots. In the end, the design can save money.

Meanwhile Eurolite has built up a very rich assortment full of different spots. An assortment which is continuously enlarged. Every delivery finally includes a double bracket enabling an additional use as floor spot. Beside the different sizes of the spots the main differences can be seen in the illuminants. A choice of single LEDs, bicolor, tricolor and quadcolor LEDs is offered.

Features:

- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Comfortable addressing and setting via control panel with LED display
- Functions: Static colors, RGB color blend, internal programs, dimmer, strobe, sound-control
- Operable in stand-alone mode or via DMX
- Master/Slave for parallel operation of several devices
- DMX512 control via regular DMX-controller
- Number of DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Microphone-sensitivity adjustable via rotary-control on the top panel

Logistic

EAN / GTIN: 4026397382822

Weight: 2,15 kg

Length: 0.25 m

Width: 0.25 m

Height: 0.08 m

- Ready for connection with power cord and safety plug
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- Single spot matching the KLS-401 and KLS-406 compact lightset
- 180 LEDs
- Control via sound to light via microphone
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power output:	1 x IEC connector (F) mounting version
LED type:	180
DMX channels:	3
Control:	Sound to light via microphone
Beam angle (1/2 peak):	25°
Dimensions:	Width: 24.3 cm Depth: 7 cm Height: 27 cm
Weight:	2 kg
DMX channels:	3/5
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	10 mm
LED number:	180
Beam angle:	25°
Dimensions (W x D x H):	243 x 71 x 250 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery: